

clip



Single Gas Clip Plus

*“Hibernate” your monitor when it is not in use....
extend the life of your disposable gas detection fleet.*

Gas Clip Technologies™ Single Gas Clip Plus (SGC Plus) is designed and tested for use in the coldest and hottest environments. It is ready to withstand the harshest working conditions in order to provide quality worker safety.

Introducing the SGC Plus with “Hibernate” mode. “Hibernate” mode allows you to place the detector in a rested state when not in use. Perfect for seasonal/turnaround contractors or rental fleets. When your job or turnaround is finished, simply sync the unit with our IR Link or ClipDock to place in a rested state. When you are ready to use again, simply press the power button to reactivate. With the SGC Plus, you only pay for the months the detector is in use.

- Only authorized personnel can place the detector in “hibernate” mode
- Unmatched sensor reliability for H₂S & CO
- Adjustable alarm set points and real-time gas reading capability
- 50% larger battery capacity
- Two-way IR comms for event downloads, bump tests & updates
- Programmable unit identification
- “Bump check” confirmation/identification

The world's most advanced single gas detector.

Unmatched reliability.

Features and flexibility that improve productivity.

Unequaled safety.

gasclip
technologies

www.gascliptech.com




IR Reader



"Clip Dock" Docking Station

Specifications

SIZE	81mm H x 50mm W x 28mm D 3.2in H x 2.0in W x 1.1in D
WEIGHT	76g 2.7oz
TEMPERATURE	H ₂ S: -50°C to +50°C / -58°F to +122°F CO: -50°C to +50°C / -58°F to +122°F
HUMIDITY	5% to 95% non-condensing relative humidity
ALARMS	Visual, vibrating, audible (minimum 95dB)
TESTS	Full function self-test on activation and every 20 hours; continuous automatic battery tests
OPERATIONAL LIFE	Two years 4 minutes of alarm time per day
RATINGS	Complies with EMC directives 89/336/EEC IP66/67
CERTIFICATIONS	Standard(s): UL-913 & CAN/CSA-C22.2 No. 157 Class 1 Divisions 1 & 2, Groups A,B,C, and D
	ETL CLASSIFIED  Intertek 4003191
WARRANTY	3 years from activation/24 months of operational life whichever occurs first 1 year shelf life
H₂S	Measuring range: 0-100 ppm Low alarm limit: 10 ppm High alarm limit: 15 ppm
CO	Measuring range: 0-300 ppm Low alarm limit: 35 ppm High alarm limit: 200 ppm
NOTES	Real-time gas display or time remaining; adjustable alarm set points and bump check reminder

gasclip
technologies

1805 Owen Court, Suite 119 Direct: (817) 453-0808
Mansfield, Texas 76063 USA Toll Free: (877) 525-0808
Web: www.gascliptech.com Fax: (817) 453-0837

Distributed By: