



SHOWA

B0502

White

Polyurethane palm coating over white nylon/polyester liner.

FEATURES

- Embossed Polyurethane palm finish Smooth grip
- EN388 Abrasion resistance level 3
- Ultra-light weight. Depending on size 6.5g 9.5g
- Ergonomic SHOWA design hand mould that replicates the natural hand form.

BENEFITS

- A light, elastic low-lint glove.
- The Finger thickness: 0.79mm provides an excellent level of tactility and sensitivity.
- PU coating resists to oils and abrasion while remaining elastic.
- A flexible glove designed for easy movement and extended wear.
- Seamless knit designed to prevent irritation.
- No latex allergy risks.

INDUSTRY



Aerospace



Agriculture



Automotive



DIY



Electronics



Manufacturing



Mechanical



Warehousing & Distribution

IDEAL APPLICATIONS

- Mechanical and engineering
- Automotive repairs & maintenance
- Intricate parts handling
- Cleanroom
- Integrated circuits
- Cleanrooms
- Component Assembly
- Mechanical engineering
- Mounting & dismantling



- MATERIAL
- Nylon
- Polyester
- Seamless knit

COATING

Polyurethane



NORMS









SHOWA

B0502

White



PACKAGING

- 10 Pair per polybag
- 24 Polybags per case
- 240 Pair per case



SIZES

- 6/S
- 7/M
- 8/L
- 9/XL
- 10/XXL



COLOUR

White





YOU MIGHT ALSO BE INTERESTED IN

SHOWA **B0502**



MATERIAL Nylon COATING Polyurethane CATEGORY General Purpose

USER INSTRUCTIONS

Do not use where there are chemical, electrical, thermal or entanglement risks. Wash at 40°C max. Performance levels as per standard EN388 retained after 3 washes, subject to variations linked to actual usage conditions. The performance levels apply to the coated surface only. Store in a dry place, away from the light.

DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

