

EN 407:2004



X 2 X X X X



Dry



Wet



Heat



Oily



Cold



Chemical



TG180

A fully coated X-Dura Nitrile Foam water resistant Cut 1 glove. Features an elastic wrist opening for easy donning, for use in wet and dry conditions. Can be worn with TG105 thermal liner in cold weather.

Key Features

- Flexible and very comfortable
- Fully water resistant red SoFlex™ coating
- Hard wearing
- Good abrasion resistance

Ideal for

- Construction and Utility
- Warehousing and Logistics
- Waste, Recycling and Local Authority
- Oil and Gas

| | | | |
|----------------|-------|-------------------|---------|
| Sizes: | 7-11 | Gauge: | 15gg |
| Liner: | Nylon | Coating: | SoFlex™ |
| No/Bag: | 10 | No/Carton: | 100 |

TG180

Glove Specifications

Glove lengths

210mm-250mm

Glove Weight

15 gauge

Liner Type

Nylon

Glove colour

Pantone 1795c / R:223 G:59 B:48 / C:8 M:96 Y:100 K:1

Overlock Colours

| SIZE | XS-6 | S-7 | M-8 | L-9 | XL-10 | 2XL-11 | 3XL-12 |
|--------|------|-----|--------|-------|--------|--------|--------|
| COLOUR | BLUE | RED | ORANGE | WHITE | YELLOW | BLACK | GREEN |

Coating Specifications

Coating colour

Red

Dip type

SoFlex™

Dip Application

Complete coating

Glove Treatment

SoFlex™



Packaging Information

Qty/bag

10 pairs

Qty/carton

200 pairs

Carton Dimensions

300mm x 600mm x 300mm

Maintenance

Both new and used gloves should be inspected to ensure no damage is present prior to use. A light gentle wash up to 3 washing cycles with mild detergent without involvement of any sort of bleaching agents. No tumble drying, just line dry at low temperature up to 30 degree Celsius.

Storage

Gloves should be ideally stored in cool, dry conditions away from excessive heat and in its original packaging.

Disposal

Used protective gloves can be contaminated or infected with harmful substances. Dispose of the gloves as instructed by your local authority.