

SAFETY JOGGER

TACTICAL



TACTICAL

ARMOUR 02

Mid-cut allround tactical boot

Upper	Waterproof Leather
Outsole	EVA/Rubber
Toecap	
Midsole	
Lining	Coolmax Mesh, Sympatex Membrane
Footbed	SJ foam footbed
Safety category	EN ISO 20347 - O2 / SRC, WR, HI, CI, FO, HRO
Sample weight	0.535 gr.
Size range	EU 36-48 / UK 3.5-13.0 / US 4.0-13.5 / CM 23.5-31.5



BLK



SYMPATEX® LINING

Keeps your feet dry and comfortable in all weather conditions.



COOLMAX® LINING

Coolmax® technology was originally developed for athletes. The material transports moisture and sweat, so that the body stays dry. We found it extremely suitable for people who work hard for hours every day too.



WATERPROOF (WR)

Waterproof footwear prevents liquids to enter into the shoe.



HEAT RESISTANT OUTSOLE (HRO)

The outsole resists high temperatures up to 300°C.



ANTISTATIC

Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm



OIL & FUEL RESISTANT

The outsole is resistant against oil and fuel.

SAFETY JOGGER
WORKS

INDUSTRIAL PROFESSIONAL TACTICAL

WWW.SAFETYJOGGER.COM

ENGINEERED
IN EUROPE

SAFETY JOGGER

TACTICAL



TACTICAL

ARMOUR 02

Industries:

Tactical, Uniform

Environments:

Muddy environment, Uneven surfaces, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.



	Description	Measure unit	Result	EN ISO 20347
Upper	Waterproof Leather			
	Upper: permeability to water vapor	mg/cm ² /h	4.2	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	39	≥ 15
Lining	Coolmax Mesh, Sympatex Membrane			
	Lining: permeability to water vapor	mg/cm ² /h	3.4	≥ 2
	Lining: water vapor coefficient	mg/cm ²	27	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance	cycles	400	≥ 400
Outsole	EVA/Rubber			
	Outsole abrasion resistance (volume loss)	mm ³	68	≤ 150
	Outsole slip resistance SRA: heel	friction	0.33	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.35	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.13	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.19	≥ 0.18
	Antistatic value	MegaOhm	163.9	0.1 - 1000
	ESD value	MegaOhm	NA	0.1 - 100
	Heel energy absorption	J	34	≥ 20
Toecap				
	Impact resistance toecap (clearance after impact 100J)	mm	NA	≥ 14
	Compression resistance toecap (clearance after compression 10kN)	mm	NA	≥ 14
	Impact resistance toecap (clearance after impact 200J)	mm	NA	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	NA	≥ 14

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Sample size:
41