

# SAFETY JOGGER

## TACTICAL

TACTICAL

## DUNE OB

### High-cut all round desert boot

Dune is a comfortable and robust boot which forms an essential part of the equipment of soldiers on active duty. It adapts to the natural shape of your feet and ensures that you remain feeling fresh and comfortable, even after a long march. The outsole guarantees a firm foothold on surfaces such as sand, stones, snow or mud. This keeps your feet pleasantly cool on long working days.

Upper	Textile, Waterproof Suede
Outsole	Rubber
Toecap	
Midsole	
Lining	Mesh
Footbed	EVA
Safety category	EN ISO 20347 - OB / SRA, FO, HRO
Sample weight	0.660 gr.
Size range	EU 38-47 / UK 5.0-12.0 / US 5.5-13.0 / CM 25.0-31.0




COOLMAX



#### ANTISTATIC

Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm



#### BREATHABLE UPPER

Increased moisture and temperature management for extended wearer comfort.



#### SRC SLIP RESISTANCE

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



SND

SAFETY  
JOGGER  
WORKS

INDUSTRIAL PROFESSIONAL TACTICAL

WWW.SAFETYJOGGER.COM

ENGINEERED  
IN EUROPE



## DUNE OB

### Industries:

Tactical

### Environments:

Dry environment, Uneven surfaces

### Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Upper	<b>Textile, Waterproof Suede</b>			
	Upper: permeability to water vapor	mg/cm <sup>2</sup> /h	6.0	≥ 0.8
	Upper: water vapor coefficient	mg/cm <sup>2</sup>	51	≥ 15
Lining	<b>Mesh</b>			
	Lining: permeability to water vapor	mg/cm <sup>2</sup> /h	49.6	≥ 2
	Lining: water vapor coefficient	mg/cm <sup>2</sup>	397	≥ 20
Footbed	<b>EVA</b>			
	Footbed: abrasion resistance	cycles	400	≥ 400
Outsole	<b>Rubber</b>			
	Outsole abrasion resistance (volume loss)	mm <sup>3</sup>	89	≤ 150
	Outsole slip resistance SRA: heel	friction	0.36	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.38	≥ 0.32
	Outsole slip resistance SRB: heel	friction	NA	≥ 0.13
	Outsole slip resistance SRB: flat	friction	NA	≥ 0.18
	Antistatic value	MegaOhm	NA	0.1 - 1000
	ESD value	MegaOhm	NA	0.1 - 100
	Heel energy absorption	J	NA	≥ 20
Toecap				
	Impact resistance toecap (clearance after impact 100J)	mm	NA	≥ 14
	Compression resistance toecap (clearance after compression 10kN)	mm	NA	≥ 14
	Impact resistance toecap (clearance after impact 200J)	mm	NA	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	NA	≥ 14

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Sample size:  
41