




**SPORTS**

## **YUKON S1P**

**Durable, light yet comfortable safety shoe**

Yukon safety shoe is a very lightweight, stylish safety shoe with excellent wearing comfort thanks to unique adaptable fitting. The breathable upper material and the lightweight footbed makes sure that Yukon is offering a best quality ventilation experience to keep your feet dry and cool all day. We have engineered this safety shoes to be extremely comfortable without feeling a sense of fatigue or discomfort. Some say it feels like having a sock on your feet.

Upper	Textile
Outsole	PU, PU/PU
Toecap	Steel
Midsole	Anti-puncture Textile
Lining	3D-Mesh, Textile
Footbed	SJ foam footbed
Safety category	EN ISO 20345 - S1P / SRC
Sample weight	0.490 gr.
Size range	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 / CM 23.0-31.5




### **BREATHABLE UPPER**

Increased moisture and temperature management for extended wearer comfort.



### **SRC SLIP RESISTANCE**

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



### **SJ FLEX**

Metalfree puncture resistant material, which is lighter and more flexible than steel. The material is not thermal conductive. Covers 100% of the surface of the last bottom.



### **ANTISTATIC**

Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm



**SPORTS**

## **YUKON S1P**

**Industries:**

Automotive, Catering, Food & beverages, Logistics, Medical

**Environments:**

Dry environment

**Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.



<b>Description</b>		<b>Measure unit</b>	<b>Result</b>	<b>EN ISO 20345</b>
<b>Upper</b>	<b>Textile</b>			
	Upper: permeability to water vapor	mg/cm <sup>2</sup> /h	30.9	≥ 0.8
<b>Lining</b>	Upper: water vapor coefficient	mg/cm <sup>2</sup>	248	≥ 15
<b>Lining</b>	<b>3D-Mesh, Textile</b>			
	Lining: permeability to water vapor	mg/cm <sup>2</sup> /h	23.2	≥ 2
<b>Footbed</b>	Lining: water vapor coefficient	mg/cm <sup>2</sup>	187	≥ 20
<b>Footbed</b>	<b>SJ foam footbed</b>			
	Footbed: abrasion resistance	cycles	400	≥ 400
<b>Outsole</b>	<b>PU, PU/PU</b>			
	Outsole abrasion resistance (volume loss)	mm <sup>3</sup>	57.0	≤ 150
	Outsole slip resistance SRA: heel	friction	0.35	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.35	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.13	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.18	≥ 0.18
	Antistatic value	MegaOhm	54.6	0.1 - 1000
	ESD value	MegaOhm	NA	0.1 - 100
	Heel energy absorption	J	23.0	≥ 20
<b>Toecap</b>	<b>Steel</b>			
	Impact resistance toecap (clearance after impact 100J)	mm	NA	≥ 14
	Compression resistance toecap (clearance after compression 10kN)	mm	NA	≥ 14
	Impact resistance toecap (clearance after impact 200J)	mm	14.5	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	20.0	≥ 14

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Sample size:  
42