

CleanAIR® Pressure

Compressed air system



Description

Systems CleanAIR® Pressure is a constant flow supplied air respirator. The regulator adjusts the amount of air coming into the headtop.

Application

Manufacturing and automotive industry – welding, grinding, surface finishing operations, suitable to the heavy industrial environments.

TECHNICAL DATASHEET

CleanAIR® Pressure

Compressed air system



Technical specification

Product code	63 00 00
Flow rate [lpm]	160 lpm - 400 lpm [adjustable]
Battery	none
Weight	250 g
Dimensions	143 mm / 110 mm / 50 mm
Noisiness	< 61 dB
Materials	Unit: high performance polyamide Belt: textile part - polyester/nylon/rubber foam plastic part - polyamide
Motor	Ball-bearing brushless motor
Inlet connection	Compatible with RECTUS 25, 26 and CEJN 320
Output [threads]	Airflow output thread - CA40x1/7" - 1x
Belt - waist size:	Comfort padded belt - up to 1 500 mm
Inlet pressure	300 - 1000 kPa
Standard Protection class / NPF***	EN 14594 class 2A / 500
Storage conditions	- 10°C to + 55°C, humidity 20 - 95 % Rh
Operating conditions	+ 0°C to + 60°C, humidity 20 - 95 % Rh

Product sets / variations

63 00 00	CleanAIR® Pressure with comfort belt and flow indicator
63 00 00W	CleanAIR® Pressure

Spare parts and accessories

71 00 60	Light flexi hose QuickLOCK™ - CA40x1/7"
71 00 86	Rubber hose QuickLOCK™ - CA40x1/7"
61 00 30	Standard hose 10 m for CAP
61 00 31	Antistatic hose 10 m for CAP
61 00 38	Standard hose 25 m for CAP
61 00 39	Standard hose 50 m for CAP
61 00 46	Spiral hose 10 m for CAP, mechanically resistant - mod.
70 00 95	Belt for CA Pressure
71 00 93	Comfort belt Standard
72 00 93	Leather comfort belt
63 00 10	Noise silencer
61 00 50	CA Pressure Conditioner with stand
70 00 90RD	Air flow indicator

Disclaimer Notice

All the information contained herein is believed to be accurate and is subject to change without notice. Users should independently evaluate the suitability of each product for their own applications. CleanAIR® products are not designed for, and may not be used in, all applications.

TECHNICAL DATASHEET

CleanAIR® Pressure

Compressed air system



Compatible headtops

72 01 02B	Short protective hood CA-1, blue	3A
72 01 02	Short protective hood CA-1, orange	3A
72 01 12	Short protective hood CA-1+, orange	3A
72 01 12B	Short protective hood CA-1+, blue	3A
72 02 02B	Long protective hood CA-2, blue	3A
72 02 02	Long protective hood CA-2, orange	3A
72 10 02	Chem-proof protective hood CA-10	3A
72 03 00.01	Protective face shield UniMask, grey	3B
72 03 00.02	Protective face shield UniMask, blue	3B
72 03 00.03	Protective face shield UniMask, orange	3B
72 03 00.04	Protective face shield UniMask, red	3B
72 03 00.08	Protective face shield UniMask, neoprene	3B
70 31 00	Protective faceshield Omnira air	TH3
71 03 00	Grinding shield CA-3 (polycarbonate visor)	2A
71 03 01	Grinding shield CA-3 (acetate visor)	2A
71 04 01*	Safety helmet CA-4 orange face seal	3A
71 04 03*	Safety helmet CA-4 additional flip-up visor, earmuffs, orange face seal	3A
70 40 01	Safety helmet CA-40 weld. shield, ADF V9-13 DS	3B
70 41 00	Safety helmet CA-40G grinding shield	3B
70 42 01	Safety helmet CA-40GW grinding + welding shield, ADF V9-13 DS	3B
70 30 01	Welding helmet CleanAIR® Verus air, incl. ADF S60+	TH3
70 32 01	Welding helmet CleanAIR Omnira COMBI air, incl. ADF S60F	TH3
70 20 70	Welding hood CA-20 ADF V9-13 DS	3B
70 20 81	Welding hood CA-20 ADF V6-8/9-13 GDS	3B
70 29 01	Welding hood CA-29 Evolve ADF V9-13 DS	2B

Disclaimer Notice

All the information contained herein is believed to be accurate and is subject to change without notice. Users should independently evaluate the suitability of each product for their own applications. CleanAIR® products are not designed for, and may not be used in, all applications.