PRIMERO AIR HI VIZ CE KAJK





TECHNICAL DETAILS



MATERIAL

EXTERNAL SHELL: HD Polypropylene

INTERNAL SHELL: HD Expanded Polystyrene

HEADBAND: Soft PA Nylon



SIZE

Universal-adjustable



WEIGHT

TECHNOLOGIES

460 g



STANDARD

EN 397 EN 50365 (Class 0) ★ Protection against top, front, rear and side impacts in conformity with EN 12492 Clauses 4.2.1 shock energy absorption capacity Clause 4.2.2 penetration







LATERAL ADJUSTMENT DIVIDER

Side regulator point on chinstrap for adjustment and positioning for a more tailored fit.



HD EPS INTERNAL SHELL

POLYPROPILENE HD EXTERNAL SHELL

(-30°C). Resists yellowing and degradation.

Inner shell composed of high-density foam for all-around impact energy absorption and improved comfort.

Lightweight external shell with exponential better performance.

Excels in impact absorption, especially at lower temperatures



Enhanced padding attachment system that quickly secures into place and allows for easy replacement, and removal. Patented system improves padding durability.



A quick-drying fabric with moisture-wicking technology that accelerates the dispersion of sweat to the surface of the helmet padding for a drier, more comfortable wear.



Helmet size adjusting system that allows for an easy and secure fit by turning the large diameter dial. The system moves up and down to adapt to a range of head shapes. The ergonomically shaped wings cradle the back of the neck for added comfort.



ADVANCED LITE CHINSTRAP

Chinstrap with 5 adjustment points for a personalized fit. Accommodates wider head sizes and adapts to earmuff use. Color-coded fasteners indicate EN standard compliance rating.



RING TO HOOK

Chinstrap loop that enables the wearer to securely attach the helmet to a harness or other items.



EARMUFF ATTACHMENT SLOTS

Helmet designed with standard 30mm EURO slots for attaching KASK hearing protection earmuffs.



VENTILATION CHANNELS

Designed with 14 air intakes shaped to prevent debris entry and internal channels for enhanced breathability and wearer comfort.



EARPLUG HOOKS

Lamp clip feature that holds corded earplugs.



FRONTAL ACCESSORY SLOT

Front attachment point for advanced customization and easy integration of accessories such as badge holders and headlamps. Includes cap cover for debris protection.









© 2023 KASK SPA. All rights reser

PRIMERO AIR HI VIZ CE KAJK

TECHNOLOGIES



NECK PROTECTOR SLOT

3 rear helmet slots for mounting KASK Neck Protection products.



EASY CLICK SYSTEM

Helmet designed with integrated slots for easy mounting of KASK eye and face protection accessories. Easy Click Visor Adapters



REPLACEABLE LAMP CLIPS

Helmet designed with 4 removable nylon lamp attachment clips. Compatible with KASK headlamps and other headlamps with elastic bands.



HI VIZ DETAILS

High visibility color shell, luminescent lamp clips and high visibility reflective adhesives for added safety in low visibility conditions.

PERFORMANCES

Protection against top impacts	K	5 kg from 1 m 50 J
Protection against side, front and rear impacts	К*	5 kg from 0,5 m 25 J
Protection against top impacts	К*	5 kg from 2 m 100 J
Protection against the penetration of objects	K	3 kg from 1 m 30 J

Chinstrap release	K	>15 kg <25 kg
Lower temperature resistance test	K	T= -30°C
Protection against side deformation	K	LD
Protection against molten metal splashes	K	ММ

K EN 397 standard requirements

K* Additional compliance in conformity with the requirements of EN12492

K EN 397 additional requirements

YEARS

10 years starting from the date of manufacture. The helmet must be checked regularly and before each use to detect the presence of any damage such as cracks, detachments, deformities, or peeling that represent factual elements of the state of deterioration of the helmet. Helmets that have suffered a severe impact shall be replaced even if they do not show obvious signs of damage.

GUARANTEE

3 years starting from the date of purchase.

ADDITIONAL INFORMATION

Clean the helmet with the KASK Helmet cleaner or with water, neutral pH soap and a soft, clean cloth. The inner lining should be washed by hand in cold water or in the washing machine (max 30°C - 85°F). The KASK Liner Refresher is available to neutralise unpleasant odours.

The helmet should be stored away from direct sunlight or source of heat. We recommend the use of the KASK drawstring helmet bag to protect the helmet when not in use.

ADHESIVE APPLICATION

Do not apply adhesives, stickers or use paint and solvents on the helmet that do not comply with the manufacturer's specifications. Any alteration or intervention may impair its protective function.

SAFETY ACCESSORIES





WVI00022-500 ZEN FACE SHIELD



ZEN FULL FACE VISOR



WVI00009/10 ZEN MM/PM VISOR



WHP00004/5/6 **EARMUFES**



DISCOVER MORE





SCAN FOR COMPLETE COLLECTION

WPA00007



WAC00013/25 NECK SHADE



WAC00032/33



WAC.00036-37











