# PRIMERO PL HI VIZ CE KAJK







# **TECHNICAL DETAILS**



#### **MATERIAL**

**EXTERNAL SHELL:** HD Polypropylene

INTERNAL SHELL: HD Expanded Polystyrene

**HEADBAND:** Soft PA Nylon



## **SIZE**

Universal-adjustable from 52 to 63 cm



# **WEIGHT**

460 g



#### **STANDARD**

EN 12492

Protection against top impacts and penetration in conformity with EN 397

Clause 5.1.1 Protection against top impacts

Clause 5.1.2 Protection against penetration

Clause 5.1.3 Flame resistance EN 397 additional tests: -30°C / LD / MM



# **TEMPERATURE OF USE**



# **CATEGORY**

# **TECHNOLOGIES**



### POLYPROPILENE HD EXTERNAL SHELL

Lightweight external shell with exponential better performance. Excels in impact absorption, especially at lower temperatures (-30°C). Resists yellowing and degradation.



## **HD EPS INTERNAL SHELL**

Inner shell composed of high-density foam for all-around impact energy absorption and improved comfort.



### CLICK-IN SYSTEM

Enhanced padding attachment system that quickly secures into place and allows for easy replacement, and removal. Patented system improves padding durability.



A quick-drying fabric with moisture-wicking technology that accelerates the dispersion of sweat to the surface of the helmet padding for a drier, more comfortable wear.



Helmet size adjusting system that allows for an easy and secure fit by turning the large diameter dial. The system moves up and down to adapt to a range of head shapes. The ergonomically shaped wings cradle the back of the neck for added comfort.



## ADVANCED LITE CHINSTRAP

Chinstrap with 5 adjustment points for a personalized fit. Accommodates wider head sizes and adapts to earmuff use. Color-coded fasteners indicate EN standard compliance rating.



### **LATERAL ADJUSTMENT DIVIDER**

Side regulator point on chinstrap for adjustment and positioning for a more tailored fit.



Chinstrap loop that enables the wearer to securely attach the helmet to a harness or other items.



## **EARMUFF ATTACHMENT SLOTS**

Helmet designed with standard 30mm EURO slots for attaching KASK hearing protection earmuffs.



# **HI VIZ DETAILS**

High visibility color shell, luminescent lamp clips and high visibility reflective adhesives for added safety in low visibility conditions.



# **VENTILATION CHANNELS**

Designed with 14 air intakes shaped to prevent debris entry and internal channels for enhanced breathability and wearer comfort.



# **EARPLUG HOOKS**

Lamp clip feature that holds corded earplugs.







# PRIMERO PL HI VIZ CE KAJK

# **TECHNOLOGIES**



### FRONTAL ACCESSORY SLOT

Front attachment point for advanced customization and easy integration of accessories such as badge holders and headlamps. Includes cap cover for debris protection.



### **NECK PROTECTOR SLOT**

3 rear helmet slots for mounting KASK Neck Protection products.



#### **EASY CLICK SYSTEM**

Helmet designed with integrated slots for easy mounting of KASK eye and face protection accessories. Easy Click Visor Adapters required.



## **REPLACEABLE LAMP CLIPS**

Helmet designed with 4 removable nylon lamp attachment clips. Compatible with KASK headlamps and other headlamps with

# **PERFORMANCES**

Protection against top impacts	K	5 kg from 2 m 100 J
Protection against side, front and rear impacts	K	5 kg from 0,5 m 25 J
Protection against the penetration of objects	K	3 kg from 1 m 30 J
Chinstrap release > 50 kg	K	
Retention system effectiveness	K	

Ventilation	K	
Lower temperature resistance test	K	T= -30°C
Protection against side deformation	K	LD
Protection against molten metal splashes	K	MM

K EN 12492 standard requirements

K EN 397 additional requirements

# ADDITIONAL INFORMATION

a severe impact shall be replaced even if they do not show obvious signs of damage.

# 3 years starting from the date of purchase.

Clean the helmet with the KASK Helmet cleaner or with water, neutral pH soap and a soft, clean cloth. The inner lining should be washed by hand in cold water or in the washing machine (max 30°C - 85°F). The KASK Liner Refresher is available to neutralise unpleasant odours.

10 years starting from the date of manufacture. The helmet must be checked regularly and before each use to detect the presence of any damage such as cracks, detachments, deformities, or peeling that represent factual elements of the state of deterioration of the helmet. Helmets that have suffered

The helmet should be stored away from direct sunlight or source of heat. We recommend the use of the KASK drawstring helmet bag to protect the helmet when not in use.

### ADHESIVE APPLICATION

Do not apply adhesives, stickers or use paint and solvents on the helmet that do not comply with the manufacturer's specifications. Any alteration or intervention may impair its protective function.

# SAFETY ACCESSORIES



WVI00007



WVI00022-500 ZEN FACE SHIELD



ZEN FULL FACE VISOR



WVI00009/10 ZEN MM/PM VISOR



WHP00004/5/6 **EARMUFES** 



WAC00036-37

## **DISCOVER MORE**





SCAN FOR COMPLETE COLLECTION



WPA00007

WAC00013/25 NECK SHADE



WAC00032/33 NECK SHIELD RW











